## PACKARD MOTOR CAR COMPANY

## DETROIT, MICHIGAN

July 6, 1934

TO BE NOTED AND INITIALED BY					
_					
		-			
		-	-		

REFER TO THIS LETTER BY NUMBER

To

PACKARD DISTRIBUTERS AND DEALERS

Subject

PACKARD SHOCK ABSORBER FLUID

## Gentlemen:

The fluid used in Packard shock absorbers when leaving the factory is an especially refined preparation approved by the Packard laboratories. Two different kinds are used, as follows:

- (1) FLUID for
  PACKARD SHOCK ABSORBERS
  (Used on 6th and 7th Series)
- (2) DELCO LOVEJOY SHOCK ABSORBERS
  (Used on 6th to 11th Series, Inclusive)

Packard shock absorber efficiency and uninterrupted performance depends largely on the correct fluid used in them. PACKARD SHOCK ABSORBER fluid has been found, after exhaustive tests, to be the best medium for this purpose and is recommended by the Packard Engineering Department.

Every Packard service station should maintain a supply of both types of Packard SHOCK ABSORBER FLUID. We are prepared to supply them in neatly labeled quarts, gallons, and five gallon containers, as follows:

## PACKARD SHOCK ABSORBER FLUID

Pc. No.	Size	Quantity	Suggested Net to Dealer	Suggested List
98322	Quart "	1 to 5 6 or more	.31 qt. .25 "	.50 qt.
98323 98324	Gallon 5 gallon		1.05 gal. .93 gal.	1.70 gal.
	DE	CO TOAELOA SHOCK	ABSORBER FLUID	
98325	Quart "	1 to 5 6 or more	.31 qt.	.50 qt.
98326 98327	Gallon 5 gallon		1.05 gal. .93 "	1.70 gal.

Dealers will order in the regular way through the distributer under whom they operate. This material is subject to group "A" discount. Distributers will refer to Trade Letter No. T-2673 for distributers net prices.

Yours very truly,

PACKARD MOTOR CAR COMPANY

B. R. Horsley

Manager Service Stores Division

BRH: WJ 3(b-x) 1250 Dealers' T.L.-143